# **HAWK**



**Beyond the Limits...** 



Form Factor Sizes: 2/4/6/8U Standard server/network racks.


Part No: AITS25HWX AITS24HWX











Toll Free (IND): 1800 309 9987
Support
Sales

MSE: DL02-27485 MII: DIPP45735

2









## **Datasheet**

#### Stand-Alone Device & Independent Operation.

It is a standalone monitoring system which works as (Device)-aaS.

Therefore, neither third party PC/device/integration/ Hardware nor external application software(s) is required. Easy to set-up, operate, and maintain. For advance features accessories component are available.

For Distributed / Multi-Location businesses with MPLS/IoT/RNMS/SD-WAN/CoLo and PR-DR connectivity Architectures. (Stacking & Replication for ACTIVE/PASSIVE | ACTIVE/ACTIVE Redundancy). Check Here Buzzard (An EMS- Environmental Monitoring System Rack- Bug device) & IoT EdgE

#### Compatibility Matrix: NMS Hardware

✓ Product (Hawk)®	Xe (Enterprise Edition)	
✓ Configuration	XE	Description
✓ RAM	16/32 Slot	DDR4/DDR5- ECC
✓ Processing platform	Intel	Intel Xeon latest Gen Scalable
	(Multi Core)	dual/quad socket processors (CPU) TDP up to 350W)
✓ Network	GbE/10GE /SFP10G*	1/2 x (dual 10GbE ports)
✓ Bays Compatibility	Yes	Provision for populating up to 4 to 24 x 3.5"/2.5" HDDs/ SSD
✓ Chipset	Intel	Intel® C621/C622/C741/Higher
✓ Storage platform	RAID Type + Octane*	RAID 5/10 SATA/SSD/NVMe Opional/ additional

3

Toll Free (IND): 1800 309 9987

Support Sales MSE: DL02-27485 MII: DIPP45735









✓ Base Platform to run (environment)	Linux Linux (Inbuilt) (Inbuilt)
✓ Accessories supported	Yes BuZZ, EDGE
✓ Power	Dual / Redundant Power Supply Quad Power
✓ Expansion (I/O) ✓ Ports	Yes 4 PCI-E 3.0 x16/ 2 PCI-E 3.0 x8, Yes 2x USB 2.0, 2x USB 3.0 ,1 x VGA/HDMI (Depending over model)
✓ Hosts	Up to As per bid specifications (XXXXX) 250000*
✓ Additional Software / Third party Integration	Not Required (Check with pre-sales or Tech team for 3 <sup>rd</sup> party API integration)
✓ Additional Hardware accessories (***)	Yes (Additional Accessories – Optional like BUzz)* IoT Gateway, EdgE – IIoT4.0
<ul> <li>✓ Browser Supports (Firefox, Chrome, IE, Opera, Safari) and all major resolutions (IOT Devices, Video Wall, NOC Wall, Large monitor, Multi-monitor, Desktop, Projection)</li> </ul>	YES
✓ Operating Systems compatibility	Inbuilt (Linux)
Windows Client supported	YES
Linux Client supported	YES
MAC Client Supported	YES
<ul> <li>Virtual Machines / Hypervisors supported</li> </ul>	YES 4

Toll Free (IND): 1800 309 9987

Support Sales

MSE: DL02-27485 DIPP45735 MII:









### Unified NMS Features (Embedded Software)

Product: (Hawk)	XE Series (Enterprise)
Software Version	HXV24.06 (Latest)
✓ DCIM (Assets and Inventory) / Inventory Management System	YES DCIM (Holistic Assets Simulator)
✓ EMS Environment Monitoring System	YES (BUzz)*
✓ IP Camera	YES (Status, Stream & Record)*
✓ CCTV Monitoring System dashboard	YES (Web-Console Only)
√ NMS (Network Management System)	YES
✓ Monitoring and Management Solutions	YES
<ul> <li>Network – NMS (Monitoring &amp; Mgmt.)</li> </ul>	YES
<ul><li>System – (Server, Chassis, and VMs)</li></ul>	YES
<ul> <li>Applications performance – APM</li> </ul>	YES
<ul> <li>Websites Performance – WPM (CDN*)</li> </ul>	YES
Database Performance – DBM	YES

MSE: DL02-27485 **DIPP45735** MII:









Storage (Capacity) Monitoring – SCM	YES
✓ Custom Reports / Audit Reports	YES
✓ Change Management (Track & record)	YES
√ User / Group Access Management (UAPM)	YES
√ Threshold Management	YES
✓ Infra Multi-Topologies- (Auto Architecture level, Wireless, device dashboard Drill-down.)	YES
✓ Alerts (Incident) / Alarms / Notifications (IMS) integrated SLA Mgmt.	YES
✓ CPU Utilisation	YES
✓ Memory Utilisation	YES
✓ Storage Consumptions	YES
✓ Network Utilisation	YES
✓ Databases Utilisation	YES
✓ Power Usage Efficiency	YES
✓ Stacking & Replication	YES
<ul><li>✓ LMS &amp; SSL Certificate monitoring &amp; Mgmt.</li><li>✓ Backup &amp; Restore (Central</li></ul>	YES
Location/SAN/NAS/DAS/NFS)	YES
	YES
✓ Personalise Monitoring	YES
✓ View Theme (Day / Night)	YES
le .	

Protocols

6

Toll Free (IND): 1800 309 9987

Support

Support Sales MSE: DL02-27485 MII: DIPP45735










Product (Hawk)	XE (Enterprise Edition)
IEEE, IANA, IETF, DMTF – SNIA, MMUSIC WG,	YES
✓ Native Monitoring Protocols	YES
✓ Standard Management Protocols	YES
International Standard High-End Compliance	YES
Certified BIS Components. CE, FC, RoHS	YES
compliant components. ISO 9001:2015, 27001:2013,20001,27034, Process compliant ITILv3 and ITSM (15+ Processes), Recyclable	

#### Version Information



#### Other Useful Information

Product	Key points
Hawk	IIoT4.0 Enabled PnP Enterprise Device – Unified Network Management System (NMS) – Unified Solution for NeXT Generation IT Infrastructure

7

MSE: DL02-27485 MII: DIPP45735









Suitable (available for all categories)- Multi Vendor & Multi Protocols Compatible	XE (Enterprise series) – Large scale Industries, Enterprises, Corporations etc. (Scalable infinite with up to 250000* hosts within device capacity)
Model	XE
Additional Accessories*	Support BuZZ (EMS: Rack-Bug), IoT- Edge etc.
Туре	U-NMS Worldwide/Nationwide Standalone/Stack/Cluster Device(s) with NMS Software embedded, Linux platform along with DB Inbuilt – Web based Console
Modules of Network Monitoring Software	SNMP* Monitoring, Netconf, Restconf, SSH (TLS/SSL), APIs, Netflow, Syslog, NCM, ACIM, Physical host monitoring, rDCIM, APM, DBM, WSM, Agent
Types of Licenses	Perpetual/Subscription (*Individual hosts/node license is <b>NOT</b> required)
Agent (No additional cost)	Available in Agent less or Agent full or both (Hybrid)
Redundancy Power	Yes, Internal Redundancy for dual power (2U/4U/6U/8U as per PSU options) - Hot Swap enabled
Mounting	Standard 19" Rack L-Shape Bracket (Included) – 2U/4U/6U/8U Rail bracket (On request Only) Wall – (*back-panel holder supported) (On request Only) Stand mounting – (*Stand) (On request Only)
Power Supply	800W Redundant Platinum 80 PLUS Certified Multi-Output Power Supply Or higher (Included) Or Standard Dual Hot-swap PSU (Rack C14 PDU - 6 Amp Three Pin socket)) higher standard Or higher (Included)
Environment Temperature	Standard cooling temperature of DC / AC- Server Room Temperature

8


Toll Free (IND): 1800 309 9987
Support
Sales

MSE: DL02-27485 MII: DIPP45735









Device Info and integrated functions

Additional Details	Description I	Description II
Domain / Type	Device (IoT Enabled)- Network Monitoring Software (NMS) – All in All Solution for IT Infrastructure	NMS, DCIM (ITIM   AMS), APM, WPM, EMS, VMS, DBMS, FSO, SCM Control & Monitoring Services and many more
Modules	Network Monitoring System, Network Management System, DCIM {Data Center(s) Inventory / assets Management (ITIM   AMS)   LMS   Cabling   OFC   PUE   commissioning and decommissioning}, APM — Application Performance Monitoring, Websites Performance Monitoring, Environment Monitoring System, Video (CCTV) Monitoring System, DBMS- Database Monitoring System, SCM —Storage Control & Monitoring Services, Reports, and Audits. Auto discovers hosts.	Suitable for: Home IT office, IT Room, Server room, Computer Room, Server Hall, NOC, NAC, Integrated Command and Control Centers, Datacenters (Tier2, 3, and 4), distributed IT Infrastructure, Nationwide and Worldwide, hybrid and cloud IT, CoLo, etc.  ITSM, ITAM, ITOM, NMS (Monitoring and Mangement), APM, Websites, Reporting, Autodiscovery, Multi-Network, Multi-Location.
Туре	Standalone Device with Inbuilt Software and Web based Console	(No Additional Hardware or Software required)  **
Country Origin	Make in India	
Lot / Part No	AITS25HWX	

9

MSE: DL02-27485 MII: DIPP45735









Software Description	HXV 23.01	
Software Version & Date of Launch of Version	HXV 01.01.2023 enterprise in continuation along with HMV	01.01.2021
Web-Console Resolution	Supported FHD (<1920 x 1080) to 4K (3840 x 2160>)	Check Series and model
Licence Delivery Mode and upgrade	Electronic License (Offline / Online)	Upgrade (Through Electronic medium like DVD, Flash, USB, etc.)
Platform type	IoT enabled Hardware –Plug and Play Appliance/Server with Web based console for management and monitoring.	
Hosting &Deployment	Client's Private Cloud, Shared, Co-Location, Multi-loca or On Premises (Rack Mount, Wall Mount, and Stand	tion, VSAT, MPLS, IoT gateway, Wireless, RF network, CAN, Mount – suitable option available along with the )
Download Data sheet	URL: www.akus.co.in	
	Write us: Connect@akus.co.in, Sales@akus.co.in Visi	t us: www.akus.co.in

FAQ (Frequently asked Questions) and Quick links		
Check our latest products	CHECK NOW <u>HERE</u>	
Other relevant products in the categories	CHECK NOW <u>HERE</u>	
Download Bulk import and export data	See Bulk IO <u>HERE</u>	
Contact for PoC and Demo	(India) sales@akus.co.in, presales@akus.co.in	
Admin Guide PDF	Black Book: Download <u>HERE</u>	
Contact Technical Support (IND)	support@akus.co.in & (Toll Free): 1800 309 9987 / RMA	

Disclaimer: All content of this document belongs to āKüs®. © 2025 Akus, Ind. For sharing and use, write us: sales@akus.co.in

10

Toll Free (IND): 1800 309 9987

Support Sales

MSE: DL02-27485 DIPP45735 MII:



